

DECLARATION OF PERFORMANCE

Nr. 71880-1

Product group: 71880 Terrace screws, A4

Intended use: Load bearing timber structures

Company contact address: Ferrometal Oy
 Karhutie 9
 01900 Nurmijärvi
 FINLAND
 www.ferrometal.fi

AVCP System: Class 3

ITT tested by: Strojírenský zkušební ústav, s.p. (Notified Body No. 1015)

ITT report no: E-30-20142-13

Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Mechanical resistance and stability	See Table 1	EN 14592:2008+A1:2012
Safety in case of fire	NPD	
Hygiene, health and the environment	NPD	
Safety and accessibility in use	NPD	
Protection against noise	NPD	
Energy economy and heat retention	NPD	
Sustainable use of natural resources	NPD	

Table 1:

Product	characteristic yield moment $M_{y,k}$ [Nmm]		characteristic withdrawal parameter $f_{ax,k}$ [N/mm ²]		characteristic head pull-through parameter $f_{head,k}$ [N/mm ²]	characteristic tensile capacity $f_{tens,k}$ [kN]	characteristic torsional ratio
	thread section	smooth section	loading across the fibre	loading along the fibre			
-	-	-	-	-	-	-	-
Fix cutter terrace screw with 4 cutters ø 4.5 mm	3 295	2 404	17,67	12,85	25,14	3,81	1,67
Characteristic density of wood ρ_k [kg/m ³]	-		480		505	-	450
Durability (i.e. corrosion protection)	stainless steel 4 (Service Class 3 acc. to EN 1995-1-1)						

Place and date of issue: Nurmijärvi 30.6.2013

Name and function: Jani Koskinen, Product Manager

Signature: _____

